Bush Hog® TOUGH 320 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH Fabricated 7 Gauge Decks

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Replaceable Skids

TOUGH Heavy Duty A Frame And Tail Wheel Bracket

TOUGH 190 HP Bush Hog Gearbox

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint





MODELS	325	326	327
Cutting Width	5 ft	6 ft	7 ft
Cutting Capacity	31/2 inch diameter	3 ^{1/2} inch diameter	31/2 inch diameter
Cutting Height	2 - 12 inches	2 - 12 inches	2 - 12 inches
Dimensions (width x length)	66 x 1071/2 inches	78 x 1181/2 inches	90 x 131 inches (Lift), 90 x 182 inches (Pull)
Type Hitch	HD 3 Point Category Cat. I & II standard and Quick Hitch	HD 3 Point Category Cat. I & II standard and Quick Hitch	HD 3 Point Category Cat. II & III standard Pull Model also available
Deck Thickness	7 gauge	7 gauge	7 gauge
Sidebands	1/4 x 121/2 inches	1/4 x 121/2 inches	1/4 x 121/2 inches
Driveshaft	ASAE Cat 5	ASAE Cat 5	ASAE Cat 5
Gearbox	Heavy duty (190 HP)	Heavy duty (190 HP)	Heavy duty (190 HP)
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Driveline Protection	Slip Clutch Standard	Slip Clutch Standard	Slip Clutch Standard
Blade Holder(s)	Round	Round	Round
Blades	1/2 x 4 inch, heat treated	1/2 x 4 inch, heat treated	1/2 x 4 inch, heat treated
Blade Tip Speed	13,572 FPM	13,996 FPM	11,875 FPM
Tires	Laminated	Laminated	Laminated, dual - Lift Large laminated, dual - Pull
Minimum Tractor HP	50 PTO	60 PTO	70 PTO
Front and Rear Deflectors	Front and rear deflectors standard, chains optional, all 3 models		
Approximate Weight	1185 lbs	1400 lbs	1950 lbs Lift, 2150 lbs Pull
Warranty	1 year limited warranty with a 5 year gearbox limited warranty		
Options	Front & Rear chains	Front & Rear Chains	Front & Rear chains, Manual or hyd. adj. for pull & lift models

FEATURES • Floating A Frame